

Significant Part Number Matrix

Type		Sump/FD					Gallons		Diameter	Color	Weight / Style	Ftg. Location	Fitting	Gasket	Lid	Lid Location
V	T	1	0	5	0	0			B	A	S	S	S	S	S	S
1	2	3	4	5	6	7			8	9	10	11	12	13	14	15

REV. 5

TYPE (1-2)
AC = Aquifer
CB = Cone Bottom
CC = Crop Care Std. Sump
CM = Crop Care Box Sump
CW = Cut Away w/Sump
DW = Dualline
FM = Free Stand w/Sump
FS = Free Stand no sump
GV = Gusset Vertical
HE = Elliptical
HZ = Horizontal
IB = Inductor Blow Mold
IN = Inductor
IS = Inductor - Side mount
LP = Low Profile
OC = Open Top Cone Bottom
OP = Open Top
OT = Oval Tank
PC = PCO w/o Sump
PM = PCO w/ Sump
PU = Pickup
SB = Spot Spray blow mold
SD = Spot Spray no sump dual
SM = Spot Spray w/Sump
SP = Specialty
SS = Spot Spray / Space Saver
ST = Stackable Tote
TD = Tear Drop
VT = Vertical
WO = Water Only

SUMP/FD/TYPE (3-4)
A = Sectional (FM Left)
B = Sectional (FM Right)
BM = Blow mold (SP)
D = Deep Sump (HZ/HE)
F = Flat No Sump (HE)
FD = Full Drain (IB/IN/CB)
PU = Pick up (SS)
R = Rectangle (OP)
S = Septic (LP)
T = Aquifer (AC)

Gallons (3-7)
00025
10500
Etc.

Diameter (8)
S = Standard (or ACT ship Lid)
A = Smallest
B = Largest (or ACT Burial Lid)
C = Center Sump
G = 28" Ground Acc. Blue (ACT)
H = 28" Ground Acc. Black (ACT)
I = 16" Ground Acc Blue (ACT)
J = 16" Ground Acc. Black (ACT)
K = Opt. Baffle Kit Installed
O = Off Center Sump .
X = Special request

Color (9)
A = Light Grey
B = Black Regrind
D = Blue
E = Light Blue
F = Black XLPE
H = FDA Black
L = Light Green
N = Green
O = Opaque White
P = Natural XLPE
T = Desert Tan
V = Grey
W = Natural White
X = Dark Green
Y = Yellow

Weight / Style (10)
S = Std.
A = 10% Heavy
B = 20% Heavy
C = 30% Heavy
D = 10 % Light
E = "AS"
F = "MM"
K = "OM"
L = "RT"
M = "VM"
N = "LC"
O = "CL"
P = "FU"
Q = STD. WGT W/CODE 5
R = 10% HVY W/CODE 5
T = 20% HVY W/CODE 5
U = "UT"
X = Special Request

Fitting Location (11)
S = Std.
A = A Diagram
B = B Diagram
G = 2" MPT FD
L = Ship Loose
N = No Ftg.
M = Multiple-See Print
T = STD & Service fitting (Dualline Tanks)
X = See Print

Fitting (12)
S = Std.
3 = 3" Bolt In Flanged Banjo (10915)
4 = 2" & 3/4" Multiple
5 = 3" Bolt In Banjo w/EPDM Gasket (10910)
6 = 3/4" Bulkhead w/Anti-Vortex(10127)
7 = 1-1/4" Bulkhead w/Anti-Vortex(10151)
8 = 1-1/2" Bulkhead w/Anti-Vortex(13661)
9 = 1-1/2" & 3/4" Multiple
A = 3/4" Ace Bulkhead (13208)
B = 3/4" HD Ace Bulkhead (10484)
D = 1" Ace Bulkhead (10485)
E = 1-1/4" Ace Bulkhead (10918)
F = 1-1/2" Ace Bulkhead (10507)
G = 2" Ace Bulkhead (10508)
H = 2" H.D. Bulkhead(10912)
I = 2" S.S. Bulkhead (10490 or 10486)
J = 3" ACE Bulkhead. (12528)
K = 3" S.S. Bulkhead (10487)
L = 2" Ftg. w/ Syphon Tube (10508, 10511, & 13810)
M = 2" Ftg. w/ Long Syphon Tube (10508, 10488, & 13808)
N = No fitting
O = 3" Ftg. w/ Long Syphon Tube (13811, 13812, & 13813)
P = 2" Bulkhead w/Anti-Vortex (12516)
Q = 1/2" Ace Bulkhead (10058(item 10442(spinweld)3gal specialty))
R = 3/4" Spinweld (10239)
T = 1-1/4" Spinweld (10085)
U = 1-1/2" Spinweld (10242)
V = 1" Spinweld (10443)
W = 1/2" Spinweld (10442)
X = Other
Y = 2" SS Bolt In (10203)
Z = 3" SS Bolt In Rhino (10011)

Gasket (13)
S = Std.
A = EPDM
B = Viton
N = No gasket
X = See Print

Lid (14)
S = Std.
1 = Hinged Lid Assy. (19502/19505)
A = 2" Vented (10631)
B = 5" Vented (13696)
C = 8" Vented (10525)
D = 12" Vented (10527)
E = 16" Vented (10528)
F = 22" Vented (10530)
G = 5" Non-Vented (13748)
H = 12" Non-Vented (10526)
J = 16" Hinged Vented DHI (15082)
K = 8" Non-vented (19166)
L = 16" Non-vented (10751)
N = No lid
O = 7" Vented (12414)
P = 16" Hinged Non Vented DHI (15083)
Q = 16" Hinged HYTEK(10516)
R = 16" Precision lid (19096)
U = 7" Non-vented (12415)
V = 5" Non-vented (13748)w/ EPDM Gasket (11042)
X = See Print
Y = 5" STEP VENT (13709)
Z = 7" STEP VENT (12427)

Lid Location (15)
S = Std.
M = Multiple Lids
N = No lid
X = See Print