
Significant Part Number Matrix



WO = Water Only
VT = Vertical
TD = Tear Drop
ST = Stackable Tote
SS = Spot Spray no sump
SP = Specialty
SM = Spot Spray w/Sump
SD = Spot Spray no sump dual
SB = Spot Spray blow mold
PU = Pickup
PM = PCO w/ Sump
PC = PCO w/o Sump
OT = Oval Tank
OP = Open Top
OC = Open Top Cone Bottom
LP = Low Profile
IS = Inductor - Side mount
IN = Inductor
IB = Inductor Blow Mold
HZ = Horizontal
HE = Elliptical
GV = Gusset Vertical
FS = Free Stand no sump
FM = Free Stand w/Sump
DW = Dualline
CW = Cut Away w/Sump
CM = Crop Care Box Sump
CC = Crop Care Std. Sump
CB = Cone Bottom
ACT = Aquifer
TYPE (1-2)

R =	F	F=	P	BM	B=	A	
= Rectangle (OP)	= Full Drain (IB/IN/CB	Flat No Sump (HE)	Deep Sump (HZ/HE	= Blow mold (SP)	Sectional (FM Right)	Sectional (FM L	SUMP/FD
	N/CB)	E)	/HE)	9)	ight)	Left)	0 (3-4)

Gallons (3-7)
00025
10500
Etc.

Color (9)
A = Light Grey
B = Black Regrind
D = Blue
E = Light Blue
F = Black XLPE
H = FDA Black
L = Light Green
N = Green
O = Opaque White
P = Natural XLPE
T = Desert Tan
V = Grey
W = Natural White
X = Dark Green
V = Vallow

Υ = Yellow	X = Dark Green	W = Natural White	V = Grey	T = Desert Tan	P = Natural XLPE

I OLL	Weight / Style (10)			= Yellow	Daily Ologic
0	8 = 1-1/	7 = 1-1/	6 = 3/4"	5 = 3" B	1

S = Standard (or ACT ship Lid)
A = Smallest

B = Largest (or ACT Burial Lid) = Center Sump

		yle (10)					te		
Δ = 3/4" Δce Bulkhead (1320	9 = 1-1/2" & 3/4" Multiple	8 = 1-1/2" Bulkhead w/Anti-\	7 = 1-1/4" Bulkhead w/Anti-\	6 = 3/4" Bulkhead w/Anti-Vo	5 = 3" Bolt In Banjo w/EPDM	4 = 2" & 3/4" Multiple	3 = 3" Bolt In Flanged Banjo	S = Std.	

U = "UT"	T = 20% HVY W/CODE 5	R = 10% HVY W/CODE 5	Q = STD. WGT W/CODE 5	P = "FU"	0 = "CL"	N = "LC"	M = "MV"	L = "RT"	K = "OM"	F = "MM"	E = "AS"	D = 10 % Light	C = 30% Heavy	B = 20% Heavy	A = 10% Heavy	S = Std.	Weight / Style (10)	
			_		_									_			kanana 	I

O = Off Center Sump
X = Special request

G = 28" Ground Access (ACT)
I = 16" Ground Access Lid (ACT)

S = Std.
A = A Diagram
B = B Diagram
G = 2" MPT FD
L = Ship Loose
N = No Ftg.
M = Multiple-See Print
T = STD & Service fitting (Dualline Tanks)
X = See Print

Fitting (12)
Std.
" Bolt In Flanged Banjo (10915)
" & 3/4" Multiple
" Bolt In Banjo w/EPDM Gasket (10910)

Fitting (12)
id.
Bolt In Flanged Banjo (10915)
& 3/4" Multiple
Bolt In Banjo w/EPDM Gasket (10910)
4" Bulkhead w/Anti-Vortex(10127)
1/4" Bulkhead w/Anti-Vortex(10151)
1/2" Bulkhead w/Anti-Vortex(13661)
1/2" & 3/4" Multiple
4" Ace Bulkhead (13208)

-	_	_	_	,			_		_		_		_		_		_	_	
L = 2" Ftg. w/ Syphon Tube	K = 3" S.S. Bulkhead (10487)	J = 3" ACE Bulkhead. (12528)	l = 2" S.S. Bulkhead (10490 or 10486)	H = 2" H.D. Bulkhead(10912)	G = 2" Ace Bulkhead (10508)	F = 1-1/2" Ace Bulkhead (10507)	E = 1-1/4" Ace Bulkhead (10918)	D = 1" Ace Bulkhead (10485)	B = 3/4" HD Ace Bulkhead (10484)	A = 3/4" Ace Bulkhead (13208)	9 = 1-1/2" & 3/4" Multiple	8 = 1-1/2" Bulkhead w/Anti-Vortex(13661)	7 = 1-1/4" Bulkhead w/Anti-Vortex(10151)	6 = 3/4" Bulkhead w/Anti-Vortex(10127)	5 = 3" Bolt In Banjo w/EPDM Gasket (10910)	4 = 2" & 3/4" Multiple	3 = 3" Bolt In Flanged Banjo (10915)	S = Std.	Fitting (12)
	Z = 7" STE	Y = 5" STE	X = See Pr	V = 5" Non	U = 7" Non	R = 16" Pro	Q = 16" Hi	0 = 7" Ven	N = No lid	L = 16" No	K = 8" Non	H = 12" No	G = 5" Non	F = 22" Ve	E = 16" Ve	D = 12" Ve	C = 8" Ven	B = 5" Ven	A = 2" Ven

Gasket (13)
S = Std.
A = RDM
B = Viton
N = No gasket
X = See Print

LIQ (14)
S = Std.
1 = Hinged Lid Assy. (19502/19505)
A = 2" Vented (10631)
B = 5" Vented (13696)
C = 8" Vented (10525)
D = 12" Vented (10527)
E = 16" Vented (10528)
F = 22" Vented (10530)
G = 5" Non-Vented (13748)
H = 12" Non-Vented (10526)
K = 8" Non-vented (19166)
L = 16" Non-vented (10751)
N = No lid
O = 7" Vented (12414)
Q = 16" Hinged HYTEK(10516)
R = 16" Precision lid (19096)
U = 7" Non-vented (12415)
V = 5" Non-vented (13748)w/ EPDM Gasket (11042)
X = See Print
Y = 5" STEP VENT (13709)
Z = 7" STEP VENT (12427)

Lid Location (15)
S = Std.
M = Multiple Lids
N = No lid
X = See Print

P = 2" Bulkhead w/Anti-Vortex (12516)
Q = 1/2" Ace Bulkhead
(10058(item 10442(spinweld)3gal specialty))
R = 3/4" Spinweld (10239)
T = 1-1/4" Spinweld (10085)
U = 1-1/2" Spinweld (10242)

O = 3" Ftg. w/ Long Syphon Tube (13811, 13812, & 13813)

M = 2" Ftg. w/ Long Syphon Tube (10508, 10488, & 13808)

(10508, 10511, & 13810)

N = No fitting

W = 1/2" Spinweld (10442) V = 1" Spinweld (10443)

X = Other

Y = 2" SS Bolt In (10203) Z = 3" SS Bolt In Rhino (10011)